

CS-16C II

6.5" In-Ceiling Speaker



CS-16W

6.5" In-Wall Speaker



KLIPSCH PERFORMANCE AT AN INCREDIBLE VALUE

Using the same design principles of our premium architectural and box speaker lines, the all new Klipsch Custom series delivers true Klipsch sound to any budget. With a 6.5" Polymer woofer and a 1" Polymer Dome tweeter the CS-16C II brings dynamic, powerful, detailed Klipsch sound to your distributed audio or home theater system. The CS-16W utilizes the same 6.5" Polymer Woofer and combines it with a 1" Polymer Tweeter for outstanding in-wall performance.

PATENT-PENDING SKYHOOK™ TOOL-FREE INSTALLATION SYSTEM

The exclusive installation system engages the dog legs automatically when the speaker is inserted into the cutout hole with a preset clamping force, eliminating the possibility of overtorquing. This fast, easy installation system reduces install time by up to 75%.

ALL NEW, BEZEL-FREE MAGNETIC GRILLE

A completely redesigned powdercoated magnetic steel grille eliminates the bezel for seamless, pristine integration into the living space.

| CS-16C II SPECIFICATIONS | |
|--------------------------|---|
| FREQUENCY RANGE | 57Hz - 20kHz +/- 3dB |
| HIGH FREQUENCY DRIVER | 1" (2.54cm) Polymer Dome Tweeter |
| LOW FREQUENCY DRIVER | 6.5" (16.51cm) Polymer Woofer |
| SENSITIVITY | 91 dB @ 2.83V / 1m |
| POWER HANDLING | 40W RMS / 160W Peak |
| IMPEDANCE | 4 0hm |
| ENCLOSURE MATERIAL/TYPE | ABS/Infinite Baffle |
| FINISH | Black Baffle/Frame, White Paintable Grille |
| PRODUCT DIMENSIONS | 9.2" W x 9.2" H x 4.5" D (23.3cm H x 23.3cm W x 11.3cm D) |
| MOUNTING DEPTH | 4.34" (11.03cm) |
| CUTOUT DIMENSIONS | 8.3" (21.1cm) |
| PRODUCT WEIGHT | 7 lbs (3.18kg) |
| INCLUDED IN BOX | Flat Paintable Magnetic Grille |
| INSTALL KIT | IK-650-C (Sold Separately) |
| FIRE RATED ENCLOSURE | ME-650-C (Sold Separately) |
| BUILT FROM | 2017 |

| FREQUENCY RANGE | 31 HZ - ZUKHZ +/- 3UD |
|-------------------------|---|
| HIGH FREQUENCY DRIVER | 1" (2.54cm) Polymer Tweeter |
| LOW FREQUENCY DRIVER | 6.5" (16.51cm) Polymer Woofer |
| SENSITIVITY | 91 dB @ 2.83V / 1m |
| POWER HANDLING | 40W RMS / 160W RMS |
| IMPEDANCE | 4 Ohm |
| ENCLOSURE MATERIAL/TYPE | ABS/Infinite Baffle |
| FINISH | Black Baffle/Frame, White Paintable Grille |
| PRODUCT DIMENSIONS | 9.0" W x 14.1" H x 3.9" D (22.8cm H x 35.8cm W x 9.8cm D) |
| MOUNTING DEPTH | 3.78" (9.6cm) |
| CUTOUT DIMENSIONS | 13" H X 8" W (33.0cm H X 20.3cm W) |
| PRODUCT WEIGHT | 7.2lbs (3.25kg) |
| INCLUDED IN BOX | Flat Paintable Magnetic Grille |
| INSTALL KIT | IK-650-W (Sold Separately) |
| FIRE RATED ENCLOSURE | ME-650-W (Sold Separately) |
| BUILT FROM | 2017 |

57Hz - 20kHz +/- 3dB



CS-16W SPECIFICATIONS

FREQUENCY RANGE