


STEREO SPEAKER + TURNTABLE PACK

Klipsch
REFERENCE



**TURNTABLE
READY**



**LOW
VIBRATION
MOTOR**

R-15PM & PRO-JECT PRIMARY TURNTABLE PACK

**A HIGH PERFORMANCE, NO NOISE, LOW FLUFF, PLUG AND PLAY
BOX OF ROCK.**



**SMARTPHONE
READY**



**HIGH
FIDELITY
CARTRIDGE**

EXPERIENCE TRUE HIGH FIDELITY SOUND


No receiver required. Just add vinyl. The R-15PM powered monitors with built-in phono pre-amp are perfectly matched to the custom Klipsch x Pro-Ject Primary turntable to deliver room-filling sound without the hassle of setting up mounds of equipment.



**COMPUTER
READY**

THE SPEAKERS

Crisp and detailed sound comes thanks to a true two-way speaker with Klipsch's legendary 90x90 Linear Travel Suspension (LTS) Tractrix horn, rigid Injection Molded Graphite (IMG) woofer, and tuned rear-firing bass port. All this horn-loaded nectar is powered by Klipsch-customized and fully integrated high resolution amplifier, jam-packed with every connection you need. Add subwoofer to taste. Use the included remote to do everything else.



TV READY




**NO NOISE
BELT DRIVE**

THE TURNTABLE

Pro-Ject's special edition Primary turntable is expertly hand-crafted to extract the every last detail from the vinyl grooves of your favorite LPs. Packing a low vibration synchronous AC motor, a perfectly-matched 8.6" aluminum tone-arm, and an audiophile-grade, low-distortion Ortofon OM 5e magnetic cartridge, the Pro-Ject Primary and R-15PM powered monitors are a match made in heaven.



**SUBWOOFER
READY**



**PLUG AND
PLAY SETUP**

THE SETUP

No pre-amp required, no receiver needed, and no need to mess with counterweights or skating adjustments. Find a wall outlet, setup the turntable and speakers, plug them in, and flip the switch: you're ready to rock.



**REMOTE
INCLUDED**



**SAFE
FOR YOUR
COLLECTION**

STEREO SPEAKER+ TURNTABLE PACK

Klipsch
REFERENCE



R-15PM

FREQUENCY RESPONSE	62 Hz - 24 kHz +/- 3 dB
LOW FREQUENCY EXTENSION	54 Hz
CROSSOVER FREQUENCY	1800 Hz
HIGH FREQUENCY DRIVER	1" (2.54cm) Aluminum diaphragm compression driver mated to 90° x 90° square Tractrix Horn
LOW FREQUENCY DRIVER	5.25" (13.3cm), copper spun magnetically shielded IMG woofer
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass-reflex via rear-firing port
INPUTS	<ul style="list-style-type: none"> • 1 x pair of RCA phono level inputs with switch for Phono/Line input versatility (Phono Preamp with ground screw terminal) • 1 x USB digital audio from a PC or Mac single RCA line level output for connection to sub. • 1 x Digital optical • 1 x 3.5mm mini jack line level • Bluetooth® wireless technology
HEIGHT	12.5" (31.8cm)
WIDTH	7" (17.8cm)
DEPTH	8.11" (20.6cm)
WEIGHT	10.3 lbs. (4.67 kg)
FINISH	Brushed Black Polymer Veneer

PRO-JECT PRIMARY

DRIVE SYSTEM	Belt-drive with silicon belt
NOMINAL SPEEDS	33/45 RPM
MOTOR	Low-vibration synchronous AC motor, DC driven AC motor control
SPEED VARIANCE	33: 0.2% 45: 0.18%
WOW AND FLUTTER	33: 0.14% 45: 0.13%
SIGNAL TO NOISE	65dB
TONE-ARM	8.6" Aluminum - Custom Matched to Ortofon OM 5E Cartridge
CARTRIDGE	Ortofon OM 5E Magnetic
INCLUDED ACCESSORIES	RCA cable, Acrylic Dust Cover, Felt Mat, 15V/500mA DC universal power supply
POWER CONSUMPTION	4.5W
HEIGHT	4.4" (11.2cm)
WIDTH	16.5" (42.0cm)
DEPTH	13.0" (33.0cm)
WEIGHT	8.8 lbs. (4.0 kg)

MM-CARTRIDGE ORTOFON OM 5E

FREQUENCY RANGE	20 - 25,000 Hz
CHANNEL SEPARATION	22 dB / 1 kHz
OUTPUT VOLTAGE	4mV
RECOMMENDED LOAD IMPEDANCE	47kohms/amplifier connection - MM-input
COMPLIANCE/SYLUS TYPE	20µm/mN - elliptical
RECOMMENDED TRACKING FORCE	17.5mN
WEIGHT	5.0 g